

xpres DTF
EVOLUTION
INSTANT PEEL LITE

- Available in a wide range of sheet sizes (XP7386) & roll widths (XP7387) to suit most desktop and roll to roll printers.
- For best results, use with our Xpres DTF Evolution Hotmelt Powder (XP7382).
- Featuring a double-sided matt finish coating for optimum handling, feed & printing stability.
- Equipped with a smooth print surface that allows for higher ink loads, achieving vibrant colours without losing image clarity.
- Improved print quality & precision with reduced print noise.
- Transfers can be peeled either instantly, hot or cold.
- Applied transfers are soft & flexible with a matt finish.
- Excellent colour retention and longevity.

APPLICATION & CARE

Pressing Time: 10-15 seconds* (A second press of 5-15 seconds is recommended to improve durability)

Pressing Temperature: 150-160*

Peel: Instant in one smooth motion*

Wash temperature: up to 40°C (inside out)

Ironing: On reverse only

**Variables such as room temperature, humidity, size of design, garment type and ink load can all effect print results. Therefore, adjustments to curing times, pressing times and temperatures may be needed to achieve the best results.*

CAUTION

A well-ventilated area, protective mask, gloves and eyewear are essential when working with DTF hotmelt powder.

Hotmelt powder should NOT be applied near printing equipment. Application near print equipment increases the risk of printer damage which may not be covered under your warranty.

NOTE

We cannot offer technical support or guarantee compatibility when using Xpres DTF Evolution Lite Film or Hot-melt Powder with other manufacturer's machines or ink types.

STORAGE

Due to the absorbent nature of the DTF coating, it is extremely susceptible to humidity and moisture. To retain the products integrity, proper storage is essential.

Moisture can dramatically affect how the film accepts the ink which can reduce colour accuracy, the level of print detail & the durability of the final transfer.

Rolls & sheets should be returned to their original packaging and sealed between uses. Store away from walls and off the floor.

Recommended storage conditions - Humidity 35-65% / Temperature 10-30°C / Shelf life 1yr.